

Egs81CR Chrome Electric Griddle

Key features

- 18mm thick, machined mild steel chrome griddle plate
 - Quick heat up, even heating across plate
- Low heat emission
 - Contributes to a cooler kitchen environment
- Thermostatically controlled from 90 270°C
 - Precise temperature control
- Two independently-controlled elements
 - Save energy by only using one side during quiet periods
- · Large capacity grease collection container
 - Easy to remove and empty during service
- 360° grease trough
 - Easy to discard excess grease and debris
- · Large capacity grease collection container
 - Easy to remove and empty during service
- · Stainless steel panels with Scotch Brite finish
 - Looks great, ideal for front-of-house kitchens
- Dynamic Link System compatible
 - Integrated linking system allows quick and easy installation to create a seamless, continuous cookline

Accessories

- Fixed stand (ST80)
- Front hob rail
- Kick strip (for stand)
- Rear blanking plate (for stand)
- · Side hob extension
- · Factory fitted, adjustable castors


Similar Models

- E9581 400mm wide smooth electric griddle (F900)
- E9581R 400mm wide ribbed electric griddle (F900)
- E3481 400mm wide electric griddle (Dominator Plus)
- E3481R 400mm wide ribbed electric griddle (Dominator Plus)





E9581CR Chrome Flectric Griddle



Specification details

Electrical rating (kW)	8.8
Electrical supply voltage	400V 3N~ 50/60 Hz
Required electrical supply (A)	32
Electrical current split (A)	L1: 9.56, L2: 19.12, L3: 9.56
Element rating (kW)	4 x 2.22 (single control)
Cooking area (w x d - mm)	660 x 640
Weight (kg)	100
Weight on stand (kg)	122
Packed weight (kg)	113.5
Packed dimensions (w x d x h - mm)	1000 x 1000 x 780
GTIN number	

Short Form specification

Unit to be Falcon F900 Series electric chrome griddle top with $4 \times 2.2 \text{kW}$ elements below plate. Unit to be supplied upon adjustable feet or installed upon optional base unit.

The cooking surface will be made from 18mm thick highly polished chrome mild steel. The cooking surface will be flush with lateral units and front hob to create a plating area. The unit will be thermostatically controlled from 90 - 270°C. There will be a grease collection area surrounding the cooking zone leading to a grease collection container.

The hob will be constructed from 2mm 304 grade stainless steel. Hobs will be laser cut with right-angled edges to allow joining of units with no gaps between hobs. Exterior panels are Scotch Brite finish stainless steel. Control knobs to be marked showing temperature positions and to have a bezel behind each knob to prevent water ingress.

Installation note

Please consult local legislation with regard to installation of cooking equipment.

